

DPS-500 DC-DC Converter

Maximize PV generation and revenue with DC-coupled energy storage

FOR UTILITY-SCALE SOLAR PLUS STORAGE

This bi-directional 500kW DC-DC converter is designed to interface battery energy storage with new and existing 1000V and 1500V central inverter-based PV power plants.

The DPS-500 is ideal for utility-scale solar plus storage installations, offering advanced features including automated clipping recapture and low voltage harvesting that increase project revenues, while its DC-coupled architecture reduces installation and regulatory costs.

This DC-DC converter can operate in voltage, current, and power control modes, and is capable of on-the-fly switching between modes. Designed to be easily scaled, any combination of up to six units can be paralleled together to create building blocks of up to 3MW of storage power.

Key Technologies

- Clipping Recapture
- Curtailment Recapture
- Energy Time Shifting
- Low Voltage Harvesting
- Ramp Rate Control



TECHNICAL SPECIFICATIONS

Electrical

DC Input Voltage Range (Battery Port):	100-1500V _{DC}
DC Input Voltage Range (PV Port):	100-1500V _{DC}
Maximum Power Rating:	500kW (@1000V _{DC}) 600kW (@1200-1500V _{DC})
Maximum Current Rating:	+/-500A _{DC}
Maximum Efficiency:	99%
Average Efficiency:	98.2%
Aux/Controls Power:	Customer supplied 120V, 1-ph, 60Hz, 1kVA service
	Customer supplied 230V, 1-ph, 50Hz, 1kVA service

Environmental

Operating Temp:	-25 to +55°C
Cooling:	Forced Air Cooled
Enclosure:	UL 3R/IP 54
Max Elevation:	1000 Meters Full Power, 3000 Meters with Derating
Dimensions (L x W x H):	33.5" x 39.4" x 80.5"
Weight:	1300 Lbs
Cable Connections:	Side or bottom entry

Certifications & Standards Compliance

UL 1741
UL / IEC 62109-1
IEC / EN 61000-6-4
IEC / EN 61000-6-2
CISPR 11 / EN 55011
FCC Part 15 Class A
IEEE Std C37.90.2

Hardware Protections

DC Contactor and Precharge on Battery Port

Software Protections

DC Over-voltage and Under-voltage	Over-temperature
DC Over-current	Fuse failure

User Interface

Remote Communications:	Modbus TCP/IP
Local Indicators:	Lamps on front panel indicating operation mode & alarm/fault status



DYNAPower

85 Meadowland Drive
South Burlington, Vermont USA 05403

dynamower.com

**MAKING
RENEWABLES
RELIABLE**



101 Quarry Drive
Milford, Massachusetts USA 01757

1.800.821.6412

mc2energystorage.com